

Contents

Introduction	3
Grade descriptors	4
Task 1 - Planning the installation	5
Candidate evidence	6
Task 1 - Product list	6
Commentary	9
Candidate evidence	10
Task 1 - Materials list	10
Commentary	11
Candidate evidence	12
Task 1 - Circuit design schedule	12
Commentary	12
Candidate evidence	13
Task 1 - Risk assessment	13
Commentary	13
Task 2 – Installation and Commission	14
Candidate evidence	15
Task 2 - Certificates and schedules	15
Commentary	19
Candidate evidence	20
Task 2 - Statement	20
Commentary	20
Candidate evidence	21
Task 2 – Decommissioning and safe isolation	21
Practical Observation Form	21
Commentary	22
Candidate evidence	22
Task 2 - Installation of electrical and electronic equipment	22
Practical Observation Form	22
Commentary	26
Candidate evidence	28
Task 3 - Documentation required by IET CoP ISITEE	28
Commentary	29

Introduction

The sample assessment materials within this document refers to the electrical and electronic equipment engineering sample occupational specialism assignment. The aim of these materials is to provide centres with examples of knowledge, skills and understanding that attest to distinction grade. In this document all exemplar evidence attests as examples of distinction grade. The examples provided do **not** reflect all evidence from the sample assignment as the focus of this material is the quality and standards that need to be achieved rather than the volume of exemplar evidence provided. However, the examples provided are representative of all tasks in the sample assignment. It is important to note that in live assessments a candidate's performance is very likely to exhibit a spikey profile and standard of performance will vary across tasks. Minimal threshold competence will be based on a synoptic mark across all tasks.

The materials in this GEM are separated into three sections as described below. Materials are presented against a number of tasks from the assignment.

Task - This section details the tasks that the candidate has been asked to carry out. What needs to be submitted for marking and any additional evidence required including any photograph/video evidence. Also referenced in this section are the assessment themes the candidates will be marked against when completing the tasks within it. In addition, candidate evidence that has been included or not been included in this GEM has been identified within this section.

In this GEM there is candidate evidence from:

Task 1

Task 2

Task 3

Candidate evidence - This section includes exemplars of candidates work, photographs of the work in production (or completed) and practical observation records of the assessment completed by centre assessors. This will be exemplar evidence that was captured as part of the assessment and then internally marked by the centre assessor.

Commentary section - This section includes detailed comments to demonstrate how the candidate evidence attests to the standard of minimal threshold competence by directly correlating to the grade descriptors for this occupational area. Centres can compare the evidence against the performance indicators in the marking grid descriptors within the assessor packs, to provide guidance on the standard of knowledge, skills and understanding that need to be met for distinction.

It is important to note that the commentary section is not part of the evidence or assessment but are evaluative statements on how and why that piece of evidence meets a particular standard.

Grade descriptors

To achieve a distinction, a candidate will be able to:

Demonstrate an exemplary performance that fully meets the requirement of the brief and is able to enter the industry to begin to work in the occupational area.

Demonstrate exemplary technical skills for installing components that is in line with industry standards. They will also demonstrate relevant and comprehensive knowledge and understanding of principles and processes through the tasks completed.

Work safely and make informed and appropriate use of tools, materials and equipment within the environments that they are working in. They will competently and independently interpret information and apply the technical skills to practical tasks and procedures to an exemplary standard as recognised by industry, producing an excellent quality of work that meets acceptable tolerances, regulations and standards.

Confidently attempt some complex tasks and the level of performance meets an exemplary level.

Identify causes and diagnose faults and have a thorough understanding and the skills to be able to repair and rectify them.

Consistently use accurate industry terminology in both written and verbal contexts.

Task 1 - Planning the installation

(Assessment themes: Health and safety, design and planning)

For Task 1 candidates need to produce the following pieces of evidence:

- Produce a materials and product list giving reasons for their choices. Product relates to the specialist technologies required for this installation
- Produce a circuit design schedule for the new socket-outlet circuit. Candidates should assume the actual length of circuit to be 27 m, clipped directly to a masonry surface in an ambient temperature of 25 °C
- Produce a risk assessment in relation to the removal of RCD protection as Regulation 411.3.3 in BS 7671

For illustration, the guided exemplification materials (GEM) for Task 1 contain examples of candidate evidence for the following assessment requirements only:

- Materials and product list with notes next to each item giving detailed reasons why this
 equipment is suitable
- Circuit design schedule showing all calculations
- Risk assessment in accordance with regulation 411.3.3 of BS 7671. To include assessment of Client's equipment, users, user training, use restrictions.

The following Task 1 candidate assessment requirements have not been included as example candidate evidence for this version of the guided exemplification materials.

 Assessor observation of the quality, consistency and accuracy of the research work, including details of any assistance provided.

Task 1 - Product list

Product	Supplier	Product features	Product information	Specification	Price	Quantity	Total Price
TP-LINK RE200 WiFi Range Extender - AC 750, Dual-band	Currys PC world	Boost your Wi-Fi signal further AC 750 Dual band (2.4 GHz + 5 GHz) One Ethernet port Plugs into a spare plug socket	Information Top features: - Next-generation WiFi gives you higher speeds - Dual-band WiFi with Ethernet connectivity - Practical range extending with indicator lights Next-generation WiFi Use the dual- band TP- Link RE200 WiFi Range Extender to expand the WiFi coverage in your home, giving you faster access for all WiFi devices. Using AC WiFi technology, this compact but powerful TP-Link range extender lets you establish broader wireless internet coverage around your house. You'll be able to use the TP- Link RE200 with any standard WiFi router and establish stronger dual-band connections in "dead" areas that were previously difficult to access. Get seamless wireless coverage throughout your home or office that allows you to get more done whether you're at work or play. Dual-band WiFi	OVERVIEW Type- Wall plug range extender Rating- AC 750 Data transfer speed - Up to 750 Mbps Wireless band - Dual-band (2.4 GHz + 5 GHz) CONNECTIVITY - Power socket pass through No Wired connections Ethernet port x 1 Antenna 2 GENERAL Colour White Box contents- TP-Link RE200 WiFi Range Extender RJ-45 Ethernet cable Quick installation guide Dimensions- 110 x 65.8 x 75.2 mm (H x W x D) Weight 100 g Manufacturer's guarantee 3 years	£22.99.	1 1	## £22.99

Product	Supplier	Product features	Product information	Specification	Price	Quantity required	Total Price
			The TP- Link RE200 WiFi Range Extender offers up to 750 Mbps dual-band WiFi with 300 Mbps speeds on the 2.4 GHz wireless band, and 433 Mbps over the 5 GHz band. Since it comes with an Ethernet port, you can also				
			connect devices that need a wired link such as a Smart TV or PC.				
			Practical range extending				
			Using the Smart Signal Indicator light, you'll easily be able to find the best place to put the RE200. It also offers a profile function that remembers previously connected wireless networks, saving you time.				
5 4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	TLC	Suitable for Combi Boilers LED Display Suitable for Gas, LPG, Oil & Some Electric Boilers 6 Daily Schedule Time Slots	6-Hour Heating Boost Function Automatic Frost Protection Child Lock	Hive Hub Required for Smart Control Smart Hub and Internet Connection Required	£99	1	£99

Product	Supplier	Product features	Product information	Specification	Price	Quantity required	Total Price
) j	TLC		Control and schedule power in the home or outside via touch, voice commands or app. No need for a hub, cloud costs or subscription.	Quick and easy set-up, with in-App support. Set timer schedules, countdown function or random security options. Compatible with Google Home and Amazon Alexa for smart home integration	£15	2	£15
	TLC	Smart retractive dimming kit containing front plate (CMA401), dimming receiver (RFDEL71B) and retractive switch module	Click Smart multifunction dimming receiver with switch input (RFDEL-71B), overcomes the issue of LED flicker which may occur with existing dimmers	Will dim up to 160W of dimmable LED, halogen and CFL Compatible with the majority of dimmable LED sources available Select between capacitive, LED, resistive and inductive loads Kit can be retrofitted to existing circuit	£80	1	£80
	TLC	Quinetic 6 Amp Wireless Switch Receiver	The Quinetic wireless controller with a high efficiency switching power supply has a wide voltage range with excellent stability and durability.	A load capacity of 6A relay. The Quinetic wireless controller is equipped with an in-rush current suppression function, creating a safe and durable product	£40	2	£40

Product	Supplier	Product features	Product information	Specification	Price	Quantity required	Total Price
	TLC	Wireless Quinetic energy switch and wireless receiving controller can be paired with any combination a controller can be controlled by a maximum of 10 separate switches, a switch can pair an unlimited number of controllers.	The Quinetic wireless switch has a built-in micro energy generator. The action of pressing the switch, generates enough kinetic energy to create and transmit a radio signal and switch on/off via a receiver (wireless controller) the lamp or other loads	Weatherproof IP67 On / Off Switch Dimmable when used with Dimmable Switch Receivers	£25	2	£25

These products have been selected based on the assignment brief, as per the task. The listed products have been chosen based on their compatibility and capability. When selecting the products, there were many things to consider, such as size, ratings and product features. Also, consideration of product features has been the main focus, as well as considering the cost of products.

Commentary

The candidate demonstrates thorough knowledge and understanding by producing a product list that identifies all resource products and components with accurate detail to carry out the tasks and meet the assignment brief requirements. Detailed consideration has been given to aesthetics of the finished product and the compatibility of accessories/products with other components within the task as per the specification.

The candidate has considered manufacturers literature relating to the products that will encompass relevant product requirements, which should be in line with associated legislation. Candidate has given strong and detailed justification for their choices.

Fully considers client perspective in relation to clarity of information in level of detail, terminology and it covers all equipment within the installation in full.

Health and safety has been fully considered during this task

Task 1 - Materials list

Adaptable boxes containing three terminals marked L-N-E and an indicator lamp which illuminates when energised Two-port central heating valve Heating control wiring centre Smart programmable room thermostat with control unit 3-compartment dado trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Box Mini Trunking YT2 YT2 flat bend 2 3-core PVC SWA cable 20s gland pak Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switch the wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and cables for connecting equipment and cables for connecting heating equipment and cables for connecting heating equipment and cables for connecting heating equipment and cables for connecting neutron.
terminals marked L-N-E and an indicator lamp which illuminates when energised Two-port central heating valve Heating control wiring centre Smart programmable room thermostat with control unit 3-compartment dado trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Mini Trunking YT2 2 meters Y72 flat bend 2
indicator lamp which illuminates when energised Two-port central heating valve Heating control wiring centre Smart programmable room thermostat with control unit 3-compartment dado trunking T joint for trunking 1 Cat 5e or Cat 6 data outlets 2 RJ45 connectors Box Mini Trunking YT2 2 meters YT2 flat bend 2 3-core PVC SWA cable 2 metres 20s gland pak 2 Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switch es dimmer wireless switch one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 1 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
when energised Two-port central heating valve Heating control wiring centre Smart programmable room thermostat with control unit 3-compartment dado trunking T joint for trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Box Mini Trunking YT2 2 meters YT2 flat bend 2
Two-port central heating valve Heating control wiring centre Smart programmable room thermostat with control unit 3-compartment dado trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Box Mini Trunking YT2 2 meters YT2 flat bend 2-3-core PVC SWA cable 2 metres 20s gland pak 2 Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches 2 dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Heating control wiring centre Smart programmable room thermostat with control unit 3-compartment dado trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Box Mini Trunking YT2 2 meters YT2 flat bend 2 3-core PVC SWA cable 2 metres 20s gland pak 2 Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Smart programmable room thermostat with control unit 3-compartment dado trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Box Mini Trunking YT2 2 meters YT2 flat bend 2-core PVC SWA cable 20s gland pak Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
thermostat with control unit 3-compartment dado trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Mini Trunking YT2 2 meters YT2 flat bend 2-core PVC SWA cable 20s gland pak Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
3-compartment dado trunking T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Box Mini Trunking YT2 2 meters YT2 flat bend 2-core PVC SWA cable 2 metres 20s gland pak 2 metres 2 met
T joint for trunking Cat 5e or Cat 6 data outlets RJ45 connectors Box Mini Trunking YT2 YT2 flat bend 2
Cat 5e or Cat 6 data outlets RJ45 connectors Mini Trunking YT2 YT2 flat bend 3-core PVC SWA cable 20s gland pak Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches dimmer wireless switch vireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
RJ45 connectors Mini Trunking YT2 YT2 flat bend 2 3-core PVC SWA cable 20s gland pak Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches dimmer wireless switch vireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Mini Trunking YT2 YT2 flat bend 2 3-core PVC SWA cable 20s gland pak 2 Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
YT2 flat bend 2 3-core PVC SWA cable 2 metres 20s gland pak 2 Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch 2 on/off wireless switches 2 dimmer wireless switch 1 wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A 2 socket-outlets Wi-Fi extender 1 Broadband router 1 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
3-core PVC SWA cable 20s gland pak 2 Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch on/off wireless switches dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender 1 Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch 2 on/off wireless switches 2 dimmer wireless switch 1 wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender 1 Sroadband router 1 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Metal-clad surface 2-gang 13 A switched socket-outlet Surface mounted occupancy switch 2 on/off wireless switches 2 dimmer wireless switch 1 wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A 2 socket-outlets Wi-Fi extender 1 Broadband router 1 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
switched socket-outlet Surface mounted occupancy switch 2 on/off wireless switches 2 dimmer wireless switch 1 wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender 1 Broadband router 1 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Surface mounted occupancy switch on/off wireless switches dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
on/off wireless switches dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
dimmer wireless switch wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
wireless switch receivers; one capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
capable of multi-switch one capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
capable of dimming smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
smart controlled 2-gang 13 A socket-outlets Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
socket-outlets Wi-Fi extender Broadband router 1 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Wi-Fi extender Broadband router 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
Broadband router 1 16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and
16amp isolator BSEN 60309 (Metal clad) Range of flexible cable suitable for connecting heating equipment and 50m drum
clad) Range of flexible cable suitable for connecting heating equipment and
Range of flexible cable suitable for connecting heating equipment and
connecting heating equipment and
cables for connecting switch
receivers
Consumables (Fixings etc)
Screws/plugs Boxes
Cable ties (pack) 1
Tools and Plant
Marking tool/Pencil 1
Tape measure 1
Power Drill (Battery/Mains) 1
Selection of drilling bits 1
(Steel/Masonry) 6mm etc
20mm Hole cutter/saw 1
Hacksaw 1
Pipe Grips/footprints 2

Equipment/Materials	Quantity
Adjustable spanner	2
Selection of metal files (reamer)	2/3
Electricians Knife	1
Side cutters	1
Pliers	1
VDE Screwdriver Philips/Pozi small	1
VDE Screwdriver Philips/Pozi	1
medium	
VDE Screwdriver Philips/Pozi large	1
VDE Screwdriver flat head small	1
VDE Screwdriver flat head medium	1
VDE Screwdriver flat head large	1
Cable/wire strippers	1
Hammer	1
Centre punch	1
Scriber	1
Spirt levels	2
Set square	1
Testing instrument (Multi-	1
functional)	
AVI (approved voltage indicator)	1
Clean cloths	2
PPE	
Overalls/protective clothing	
Steel toe capped boots	
Goggles/glasses	

The candidate demonstrates thorough knowledge and understanding by producing a materials list that identifies all the resources and components with accurate quantities to carry out the tasks and meet the assignment brief requirements. Excellent detail displayed, in relation to materials and tools required to successfully complete the installation task.

Information in the list is clear and logically presented with all elements considered and in line with industry requitements. Terminology used is accurate and the quantities provided are comprehensive.

Health and safety has been fully considered during this task.

Task 1 - Circuit design schedule

Circuit	06
Description	One metal-clad 2-gang 13 A switched socket-
	outlet
No. outlets	One (1)
	SWA cable (Thermosetting 90 °C) or
Type of wiring	(Thermoplastic 70°C)
Design current (lb)	16 A Assumption
Type and Nominal Rating (In)	16 A Type B
Length	27m
Installation method	Clipped Direct reference method C
Ambient Temperature	25 °C
Rating factor Ambient air temp	1.02 (On-site guide p152 table F1)
Total circuits in group	1
Rating factor for grouping	1 (On-site guide p154 table F3)
Minimum current capacity	16 A Applying factors not detrimental
mV/A/m	Based on 2.5mm CSA (3-core) 15mV/A/m
	6.48Volts acceptable as below 5% of 230V
Actual volt drop	(11.5V)
	2.5mm required as 1.5mm SWA exceeds the
Minimum conductor size	5% of 230V (11.5V)
Formula, calculations and	
literature referencing (Page	
numbers and tables used)	Iz>In/CF
shown and stated	Vd=mV/A/m x lb x L/1000

Commentary

The candidate shows excellent knowledge and understanding creating a circuit design schedule with accuracy and detail. The schedule identifies all relevant design information required to successfully complete the electrical design for this circuit.

Excellent recording and usage of electrical literature found, with page numbers and tables clearly and accurately referenced. All design criteria have been accurately completed, with all necessary calculations made and shown, in line with BS7671 and the assignment brief requirements.

Clear justifications and reasoning are provided throughout such as the minimum conductor size. Documentation detailed and included all key design information. Full consideration of technical language, and terminology, has been used throughout.

Calculations are accurate with all factors considered and working out shown in detail. All units are nominated, and calculations are presented to a uniformed number of decimal places.

Task 1 - Risk assessment

Activity: Risk assessment in accordance with regulation 411.3.3 of BS 7671 – Removal of RCD Protection

Date: 12 2 2021

Position:

Location: Workspace SEVERITY (S): Degree of harm which may be caused (including numbers affected) **RISK RATING (RR):** Severity x Likelihood 1 Minor Injury 2 Major Injury 3 Fatality 1-2 Low LIKELIHOOD (L): Probability that event will occur 3-5 Medium 1 Remote 3 Likely 6-9 High 2 Possible Are the Item Persons **Existing Controls** Hazard RR Risks Activity: 1-1-(Mitigation) No: at Risk 3 3 Controlled? 2/3 1 Removal of RCD Protection Usage of Staff/user Relevant product training 1 3 Client's needed, as well as strict instruction of the following of equipment product usage and guidelines Removal of RCD Protection Staff/user 2/3 Socket misuse Suitable training and 3 leading to instruction given, in relation electric shock to what equipment only, must be sourced through/by this socket outlet. The socketoutlet and circuit must be clearly labelled and identified for correct/designated use. (Patch panel equipment only) Removal of RCD Protection Staff/user Staff/user 2/3 1 Appropriate training and 3 component instruction given to users. Explain the restrictions associated with the socket-outlet

Commentary

The candidate demonstrates a thorough knowledge and understanding of the different types of risk and hazards associated with the tasks, having identified all key hazards and associated risks. The candidate identifies relevant controls for all of the identified risks and makes clear justification and reasoning for the control measures that are appropriate. Potential for harm and probability factors have been identified throughout.

Probability of each of the hazards/risks occurring has been considered for all risks in accordance with BS7671.

Risk mitigation methods are detailed and have been clearly identified for all potential risks

Task 2 – Installation and Commission

(Assessment themes: Health and safety, systems and components, inspection and testing, handover and communication)

For task 2 candidates need to produce the following pieces of evidence:

- Certification and schedules
- Basic O&M Manual to include all manufacturer's information and basic instructions that the client would find useful not included in manufacturer's data
- Statement relating to the safe, sustainable and legal disposal of equipment
- Assessor observations
 - Decommissioning and safe isolation
 - Installation as per client schedule
 - Inspection, testing and commissioning
 - Handover to the client

For illustration, the guided exemplification materials (GEM) for Task 2 contain examples of candidate evidence for the following assessment requirements only:

- Certification and schedules
- Statement relating to the safe, sustainable and legal disposal of equipment
- Assessor observations of the following
 - Decommissioning and safe isolation
 - Installation as per client schedule

The following task 2 candidate assessment requirements have not been included as example candidate evidence for this version of the guided exemplification materials.

- Basic O&M Manual to include all manufacturer's information and basic instructions that the client would find useful not included in manufacturer's data
- Assessor observations
 - Inspection, testing and commissioning
 - Handover to the client


Photographic evidence required:

- Evidence of the installation at one-hour stages showing progression. (photographs should only show the installation wall/board and not the candidate) (photograph 1 –
 4)
- Completed installation and equipment (photograph 5)
- Photograph showing the inside of the distribution board and SWA termination (photograph 6)

Task 2 - Certificates and schedules

INDICATIVE CONTENT.		
ELECTRICAL INSTALLATION CERTIFICATE (REQUIREMENTS FOR ELECTRICAL INSTALLATIONS - BS 7671 [IET WIRING REGULATIONS])		
DETAILS OF THE CLIENT CITY & GUILDS TLEVEZ	LTD.	
INSTALLATION ADDRESS LONDON		
DESCRIPTION AND EXTENT OF THE INSTALLATION Description of installation: SMALL CIVICA Extent of installation covered by this Certificate:	New installation	0
- 1 (ONW)	Addition to an existing installation	10
SWA - NEW CIRCUIT (SURVEY) SWRCING NEW PATCH (Use continuation sheet if necessary) PANCE. see continuation sheet No:	Alteration to an existing installation	0
FOR DESIGN I/V/é being the person(s) responsible for the design of the electrical installation (as indicated by my/oy of which are described above, having exercised reasonable skill and care when carrying out the design certificate applies to an addition or atteration, the safety of the existing installation is not impaired, hen design work for which I/v/é have been responsible is to the best of my/our knowledge and belief in acc BS 7671:2018, amended to A/Z/4 (date) except for the departures, if any, detailed as follows:	n and additionally when by CERTIFY that the	
Details of departures from BS 7671 (Regulations 120.3, 133.1.3 and 133.5): None: Details of permitted exceptions (Regulation 411.3.3). Where applicable, a suitable fisk assessment(s) must be attached to tris	Certificate.	
The extent of fiability of the signatory or signatories is limited to the work described above as the subjection.	Risk assessment attac ct of this Certificate.	thed to
For the DESIGN of the installation: *"(Where there is mutual responsibility Signature: PC JG-17-1 Date: 16/02/21 Name (IN BLOCK LETTERS): CL-17 V E J		No 1
Signature:	Designer	No 2**
FOR CONSTRUCTION I being the person responsible for the construction of the electrical installation (as indicated by my sign which are described above, having exercised reasonable skill and care when carrying out the construction work for which I have been responsible is to the best of my knowledge and belief in accordance of the departures, if any, detailed as follows:	tion hereby CERTIFY th	at the
Details of departures from BS 7671 (Regulations 120.3 and 133.5):	3	
The extent of liability of the signatory is limited to the work described above as the subject of this Certif	icate	
For CONSTRUCTION of the installation: Signature: CTCVKINI Date: 140421 Name (IN BLOCK LETTERS): CLVC J FOR INSPECTION & TESTING	G/K/A Construct	or
I being the person responsible for the inspection & testing of the electrical installation (as indicated by rof which are described above, having exercised reasonable skill and care when carrying out the inspect that the work for which I have been responsible is to the best of my knowledge and belief in accordance amended to A.J.,(date) except for the departures, if any, detailed as follows:	tion & testing hereby Cl	
Details of departures from BS 7671 (Regulations 120.3 and 133.5):		
The extent of liability of the signatory is limited to the work described above as the subject of this Certif	icate.	
For INSPECTION AND TESTING of the installation: Signature: C Journal Date: 14/62/21 Name (IN BLOCK LETTERS): C L・い C	Jenery.	
NEXT INSPECTION		
I/We the designer(s), recommend that this installation is further inspected and tested after an interval or years/months.	r not more than	

PARTICULARS Designer (No 1)				AL INSTALLATION C			INSMLUTION A
	Address:	- GRA	MUTS.	Postcode: C/	19916	₹ Tel No:	DIS 34 56 7890
Designer (No 2) (if applicable)	Name:	1/	4	Company:		N/A	
Constructor	Name:	AME AGE	- As	Company:			
Inspector	Name:		e As	Company:			
SUPPLY CHAR	CYEDIOTICS	ANDEA		Postcode:		161 NO:	
Earthing		er and Typ	se of Live	Nature of St	ipply Par	ameters	Supply Protective Device
arrangements TN-C	AC 12/ 1-phase, 2-w 2-phase, 3-w 3-phase, 3-w 3-phase, 4-w Confirmation	ire	DC 2-wire 3-wire Other	Nominal voltage, Ji Nominal frequency Prospective fault of External loop impo (Alloy engalry or (2) by engalry or	urrent, l _e /	50 Hz 2 L: G kA 0 14 Ω	BS (EN) 88 Type 2 Rated current 100 A
Other sources of		CONTRACTOR OF THE PARTY OF THE	Commence of the second		ay mossium.	resolution of the second	-
				THE CERTIFICATE			
Means of Earthi Distributor's facili Installation earth electrode	N M	pe (e.g. ro	d(s), tape etc)	of Installation Eart	h Electro	lete as appropri de (where ap	plicable)
Main Protective	Conductors				338		,
Earthing conduct	or	Material	20	csa / O	mm²	Connection	/ continuity verified 🔟
Main protective b conductors (to extraneous-cond	fuctive-parts)	,		/		B=0.0000	/ continuity verified 🗹
To water installat			s installation pip				To structural steel
To lightning prote	Control of the Contro						
Main Switch / Sv				100 A	Hech	main switch	
GRAVAS BS(EN)G.:	FLOW	3 Fu	se / device rating	230 V/AA	Rated	residual oper time delay	ating current (I _M) MA:mA ms
COMMENTS ON	A	STALLAT	ION (in the case	of an addition or alte			344.1.2):
SOME	1725	CAN	27.2	Benc N	14.06	*	
UPDATE	HEC	eno	rus	Win 5	MAG	-7 C	WINE.
SCHEDULES		4 - 11		0.05.4.1.21			
Schedule Erfor question of schedule	edules are pa is of Inspection decatached).	ns and	Schedules	Certificate is valid or of Test Results are at	ny when t tached.	ney are attac	ned to it.



SCHEDULE OF INSPECTIONS (for new installation work only) for

DOMESTIC AND SIMILAR PREMISES WITH UP TO 100 A SUPPLY

NOTE 1: This form is suitable for many types of smaller installation, not exclusively domestic.

All items inspected in order to confirm, as appropriate, compliance with the relevant clauses in BS 7671. The list of items and associated examples where given are not exhaustive.

NOTE 2: Insert √ to indicate an inspection has been carried out and the result is satisfactory, or N/A to indicate that the inspection is not applicable to a particular item.

Item No	DESCRIPTION	Outcome See Note 2
1.0	EXTERNAL CONDITION OF INTAKE EQUIPMENT (VISUAL INSPECTION ONLY)	
1.1	Service cable	
1.2	Service head	
1.3	Earthing arrangement	
1.4	Meter tails	
1.5	Metering equipment	
1.6	Isolator (where present)	N/A
2.0	PARALLEL OR SWITCHED ALTERNATIVE SOURCES OF SUPPLY	1 1/4
2.1	Adequate arrangements where a generating set operates as a switched alternative to the public supply (551.6)	1//4
2.2	Adequate arrangements where a generating set operates in parallel with the public supply (551.7)	N/A
	Symplemic minibasiems where a Teneraturif see obstates in baranet sum are brown additio (12/11)	L N/A
3.0	AUTOMATIC DISCONNECTION OF SUPPLY	
3.1	Presence and adequacy of earthing and protective bonding arrangements:	
	- Distribute's outling assurgation (342.1.2.1, 342.1.2.2)	V
	* Installation earth electrode (where applicable) (542.1.2.3)	N/A
	Earthing conductor and connections, including accessibility (542.3; 543.3.2)	V-
	 Main protective bonding conductors and connections, including accessibility (411.3.1.2; 543.3.2; 544.1) 	
	Provision of safety electrical earthing/bonding labels at all appropriate locations (514.13)	
	- RCD(s) provided for fault protection (411.4.204; 411.5.3)	N/A
1.0	BASIC PROTECTION	
l.I	Presence and adequacy of measures to provide basic protection (prevention of contact with live parts) within the installation:	,
	* Insulation of five parts e.g. conductors completely covered with durable insulating material (416.1)	V/
	Barriers or enclosures e.g. correct IP rating (416.2)	
	· · · · · · · · · · · · · · · · · · ·	
5.0	ADDITIONAL PROTECTION	
i.I	Presence and effectiveness of additional protection methods:	
	RCD(s) not exceeding 30 mA operating current (415.1; Part 7), see Itom 8.14 of this schedule	/
	+ Supplementary bonding (415.2; Part 7)	N/4
i.0	OTHER METHODS OF PROTECTION	
i.I	Presence and effectiveness of methods which give both basic and fault protection:	
	* SELV system, including the source and associated circuits (Section 414)	N/A
	PELV system, including the source and associated circuits (Section 414)	NIA
	Double or reinforced insulation i.e. Class II or equivalent equipment and associated circuits (Section 412)	N/A
	* Electrical separation for one item of equipment e.g. shaver supply unit (Section 413)	NIA
.0	CONSUMER UNIT(S) / DISTRIBUTION BOARD(S):	
	Adequacy of access and working space for items of electrical equipment including switchgear (132.12)	1
.1		
.1	Components are suitable according to assembly manufacturer's instructions or literature (\$36.4.20%)	
1.2	Components are suitable according to assembly manufacturer's instructions or literature (\$36.4.203)	
	Components are suitable according to assembly manufacturer's instructions or literature (536.4.203) Presence of linked main switch(es) (462.1.201) Isolators, for every circuit or group of circuits and all items of equipment (462.2)	



No	DESCRIPTION	See Note:
	CONSUMER UNIT(S) / DISTRIBUTION BOARD(S) continued	
1.6	Protection against mechanical damage where cobles enter equipment (522.8.1; 522.8.5; 522.8.11)	-
1.7	Confirmation that ALL conductor connections are concedly located in terminals and are tight and secure (526.1)	
7.8	Avoidance of heating effects where cables enter fenomagnetic enclosures e.g. steel (521.5)	/
7.30	Selection of concert type and unings of circuit protective devices for overcurrent and fault protection (411.3.2, 411.4, 411.5, 411.6, Sections 432, 433, 432, 532.3.1.1) Processe of appropriate directic charts, warning and either notices:	/
7.10		_
	Provision of circuit chartolychedules or equivalent forms of information (\$14.9)	V
	 Warning notice of method of isolation where live parts not capable of being isolated by a single device (\$14.11) 	N/M
	+ Prelodic inspection and testing notice (514.12.1)	
	PCD six-monthly test notice; where required (514.12.2)	-
	APDO six-monthly test notice; where required.	NA
	Warning notice of non-standard (mixed) colours of conductors present (514,14)	N/A.
11.5	Presence of labels to indicate the purpose of switchgoar and protective devices (\$14.1.1; \$14.5)	
LO	CIRCUITS	
1.1	Adoquacy of conductors for current-currying capacity with regard to type and nature of the installation (Section 523)	
8.2	Cable installation methods suitable for the location(s) and external influences (Seetina 522)	1
1.3	Segregation/separation of Band I (ELV) and Band II (LV) circuits, and electrical and non-electrical services (525)	1
1.4	Cables correctly creeted and supported throughout, with protection against abrasion (Sections 521, 522)	-
1.5	Provision of fire barriers, scaling arrangements where necessary (527.2)	1
1.6	Non-sheathed cables enclosed throughout in conduit, ducting or trusking (521.10.1; 526.0)	1
1.7	Cables concealed under floors, above orilings or in wallsquartitions, adequately	V .
	protected against damage (522.6.201, 522.6.202, 522.6.203; 522.6.204)	-
LB	Conductors concerly identified by colour, lettering or numbering (Section 514)	V
1.9	Presence, adequacy and correct termination of protective conductors (411.3.1.1; \$43.1)	
8.10	Cables and conductors correctly connected, enclosed and with no undur mechanical strain (Section 526)	
3.11	No basic insulation of a conductor visible outside enclosure (326.8)	
1.12	Single-pole dryloss for switching or protection is line confluctors only (132.14.1; 530.3.2; 643.6)	
8.13	Accessories not damaged, accurely fixed, correctly connected, suitable for external influences (134.1.1; \$12.2; Section 526)	
8.14	Provision of additional protection/regalectments by RCD not exceeding 30mA:	NA
	Suelice-outlets rated at 32 A or less, unless exempt (411.3.3)	190
3 33	Supplies for mobile equipment with a current enting not exceeding 32 A for use outdoors (411.3.3)	
- 33	Cables concealed in walls at a depth of less than 50 mm (522.6.202; 522.6.203)	-
_	Cables concealed in walls/partitions containing metal parts regardless of depth (522.6.202; 522.6.203)	12
_	Final circuits supplying luminaires within domestic (household) premises (411.3.4)	
R.1.5	Presence of appropriate devices for isolation and switching correctly located including:	-
-	Means of switching off for rechanical traintenance (Section 464; 537.3.2)	-
	• Emergency switching (465.1; 537.3.3)	11.0
_	Functional switching, for control of parts of the installation and current-using equipment (463.3; 537.3.1)	NIA
	+ Firelighter's switches (537.4)	NIA
	CURRENT-USING EQUIPMENT (PERMANENTLY CONNECTED)	
1.0		
k.i	Equipment not damaged, accusely fixed and suitable for external influences (134.1.1; 416.2; 512.2)	1
1.2	Provision of overload audior andervoltage protection e.g. for rotating machines, if required (Sections 445, 552)	N/A
1.3	Installed to reininize the build-up of heat and restrict the spread of fice (421.1.4; 559.4.1)	/
1.4	Adaptacy of working space. Accountbility to equipment (132.12; 513.1)	
0.0	LOCATION(S) CONTAINING A BATH OR SHOWER (SECTION 201)	
0.1	30 mA RCD protection for all LV circuits, equipment suitable for the zenes, supplementary bonding (where required) etc.	NA
Dec 19		-7/4
1.0	OTHER PART 7 SPECIAL INSTALLATIONS OR LOCATIONS	
1.1	List all other special installations or locations present, if any. (Record separately the results of particular inspections applied)	1/1

		1	N	C. Consu	5	FS	1	-	number		Signature	Name (Capitals)	Tested by:	Phase sequence confirmed (where appropriate)	Correct supply polarity confirmed		
		1	1	CAHOL GO	1 1	1	N	a victor based bron.			A MINISTER)	C	onfirmed (when	tarity confirmed	1.6.6	0.45
Н	+	\mathbb{H}	H	C 37.609	H	Y	4	BS (EN)	Pr	N. ini	NO TOTAL STATE	7	appropri	9		
П	1	A	M	166		1		rating (<u> </u>	Protective device		- 1					
Н	+	1	1		H	1	1	_capacit _RCD (,		9000	Data Liky			1		1	
		IX	1	WA 2K		1		Macino permits	m d Z _a (Ω*		102	1			1	4/4	
	+	\mathbb{H}	H	0	Н	1	N	Reference Wethod	-	Conduc	121	1					
	1	#	1	2.5 2.5	Н	1	H	cpc (me		Conductor details	If						
	1	M	1	1	H	1	1	rı (line)		-	98	30	T				
Н	\bot	11	1	١	1	X	N	r. (neut	al)	1	direuit continuity	Ring final				ı	
Н	+	1	4	0	H	1	4	r2 (ope)	+			Q					
	1	1		130		1		R ₂		2	70	Arrest					
	11)	N	1	200	П		M	v		Insubs To	tice Ru st Volta	-	09				
Н	+	M	1	रुस्र कर्य	Н	1	7	Live - Li			Resistance (MCs)	hulation		m	20.00	1 5	-
	†	1	V	1		1	H	a second	-		Polarit		- 1	Earth electrode resistance	RCD RUK loop impedance	Insulation registance	Descriptor.
	N			0 62 4/4	7	D	П	Maximu ,, measur	-		Ð.	7	Test results	rode res	du doo	netstan	-
Н	11		1	1/4 4/4	1	f	1	Disconno (stre (ms) RCD test	button		Ì	ğ	E .	stance	ecunce	i	
H	H)	N/A	\exists	1		Manual A & button op	FDO lest			AFDO	1			ŀ	11/4
	V	6.67	W. S. W.	13:30	Creek					/Constitution or service	(confin	Remarks		NA	W4:		046 T T 1

The candidate demonstrates a thorough knowledge and understanding of the requirements for completing certification and schedules and the EIC documents produced are thorough and detailed, as well as set out in a logical order. The documents are easy to follow and accurate in process. Clear justifications and reasoning are provided throughout. Full consideration and accurate use of technical language and terminology throughout the completed EIC. Overall documentation is excellent and fully considers both materials and equipment, and the protection of customer property, including safety and PPE.

Task 2 - Statement

Statement relating to the safe, sustainable and legal disposal of equipment

- Ensure you have the correct PPE
- Follow and adhere to all relevant health and safety documentation and regulations
- Collect all fittings that will be necessary, as well as the tools/equipment required to remove redundant components from the installation
- Safely isolate the installation/circuit, before any decommission work commences
- Obtain permission to start work
- Prove that the approved voltage indicator is functioning correctly
- Identify the source(s) of supply using an approved voltage indicator
- Isolate the supply, lock off and retain the key
- Prove the system/equipment is DEAD using an approved voltage indicator
- Prove that the approved voltage indicator is functioning correctly
- Put up warning signs to tell other people that the electrical installation has been isolated
- Once the system/equipment is proved DEAD, work can begin
- Disconnect the redundant switches in a safe working manner.
- Remove all redundant wiring associated with the switches that will not be required
- Remove any redundant containment that will no longer be required
- Make safe all alterations to this circuit and associated containment/enclosures.
- Special attention needs to be given to sustainability and recycling.
- Follow all statutory legal requirements, as stated within the WEEE regulations (Waste from Electrical and Electronic Equipment)

Commentary

The candidate demonstrates a thorough knowledge and understanding of the requirements for creating statements and the statement is logical in sequencing, detailing all aspects of the decommissioning of the redundant lighting switches. The level of detail is accurate demonstrating a comprehensive understanding of the installation processes with the primary focus on the removal of sections of the installation that will no longer be required. The methods described are accurate, providing logical reasoning, as to what actions are to be carried out during this task.

Health and safety has been considered during the preparation and throughout this task.

Full consideration given to the use of technical language and terminology throughout.

Task 2 - Decommissioning and safe isolation

Practical Observation Form

Assessment ID	Qualification number
8710-352	8710-32
Candidate name	Candidate number
Candidate A	CG12345
Centre name	Assessment theme
City & Guilds	Health and safety, systems and components (Decommissioning and safe isolation)

Complete the table below referring to the relevant marking grid, found in the assessment pack. Do not allocate marks at this stage.

Task	Notes – detailed, accurate and differentiating notes which identify areas of strength and weakness are necessary to distinguish between different qualities of performance and to facilitate accurate allocation of marks once all evidence has been submitted.
Decommissioning and safe isolation	Health and safety is followed during preparation and throughout tasks and all work completed safely. Candidate has ensured all H&S and site preparation works are in place before starting task by putting dust sheets on floor, storing tools and materials in safe location. Correct process and procedures were followed and carried out with accuracy in the allotted assessment timings. The candidate managed their time effectively throughout the process. The candidate did not require any prompting throughout the task. Candidate correctly sourced all the equipment for performing the safe isolation procedure, including signage needed and then requested permission to proceed from the assessor. The candidate correctly checked the testing equipment and confirmed operation and continued to isolate supply correctly. Tests to prove supply was DEAD had been carried out with accuracy and confirmed the installation was safe.

Task	Notes – detailed, accurate and differentiating notes which identify areas of strength and weakness are necessary to distinguish between different qualities of performance and to facilitate accurate allocation of marks once all evidence has been submitted.				
	Candidate completed the task logically, completing each component of the task and moving on to the next stage of the process. Candidate correctly erected relevant signage and placed notices to advise persons that the system was safely isolated and tested. The candidate performed all practical elements of the decommissioning				
	accuracy.				

Assessor signature	Date			
A. Assessor	22/2/21			

Candidate demonstrates an excellent understanding of the safe isolation and decommissioning process and carried out the necessary steps of the safe isolation procedure and decommissioning of lighting switches correctly. The candidate used correct terminology accurately throughout the assessment.

Health and safety is followed during preparation and throughout tasks and all work completed safely.

Candidate evidence

Task 2 - Installation of electrical and electronic equipment

Practical Observation Form

Assessment ID	Qualification number
8710-352	8710-32
Candidate name	Candidate number
Candidate A	CG12345
Centre name	Assessment theme
City & Guilds	Health and safety, Systems and components, Reports and information, Inspecting and testing of systems and components (installation)

Complete the table below referring to the relevant marking grid, found in the assessment pack. Do not allocate marks at this stage.

Task	Notes – detailed, accurate and differentiating notes which identify areas of strength and weakness are necessary to distinguish between different qualities of performance and to facilitate accurate allocation of marks once all evidence has been submitted.
	Health and safety procedures were followed accurately throughout. Candidate has ensured all H&S and site preparation works are in place before starting task by putting dust sheets on floor, storing tools and materials in safe location.
	Candidate follows correct process for the installation of system. Installation is to industry standards and is completed confidently and in a timely manner.
	Work area measured accurately in line with diagram. Marking out accurate without error.
	Component selection is appropriate and clearly links to the quality of finished installation.
	Highly competent in installation skills which is demonstrated in the quality of the finished installation.
	Excellent use of tools resulting in a high-quality installation.
	Reference made to manufacturer's instructions at all appropriate stages during the installation.
	Measurement of wiring and associated component installation is accurate and meets the design specification and is within tolerance without undue waste. Candidate requires no prompts or reassurance throughout all tasks.
	Inspection and testing is to industry standards and is completed in a timely manner.
	Use of tools is excellent resulting in a high-quality installation.
	Candidate follows correct process for the inspection and testing of circuits.
	Candidate has no gaps in the completion of the electrical installation certificate.
	Candidate follows correct process for the configuration of the circuits with all necessary software, firmware and hardware in accordance with manufacturer's information.
	Highly competent in installation skills which is demonstrated in the quality of the finished installation

Assessor signature	Date
B. Assessor	22/2/21

Tolerances have been met with overall installation of a high-quality finish.

Photographic evidence Task 2 - Installation

Evidence of the installation at one-hour stages showing progression. Photographs should only show the installation wall/board and not the candidate (photograph 1-4)

Photo: 1

Image shows the candidate is on schedule with timings at first stage. All the marking out of containment, components and equipment completed accurately and appropriately. Candidate commenced the installation of some additional containment (Dado trunking). Excellent use of tools, when fabricating task containment.

Photo: 2

Image shows the candidate has completed the installation of the SWA cabling with extreme accuracy and precision. Excellent use of tools evident with the quality of termination and glanding of the SWA cabling. The candidate is within timings at this second stage.

Photo: 3

Image shows the candidate has completed the installation of the SWA and termination of both ends, neatly and with excellent accuracy. The candidate has mounted most of the smart components, correctly and accurately.

The candidate is within timings at this third stage.

Photo: 4

Image shows the candidate has completed the installation of the containment, components, equipment and cabling, which includes the termination of SWA at both ends. In the required time to a very high-quality standard finish. All the smart Control switches have been mounted at this point. The candidate is within timings at this fourth stage.

Photo: 5

Image shows the completed installation showing all the containment, components and equipment, as a completed install/build. The candidate displayed an excellent final product, which is accurate to measurements, and is extremely neat. Excellent attention to detail evident.

Photo: 6

Image shows the inside of the distribution board, so that all wiring and connections can be seen and reviewed. Excellent quality displayed, conductors and terminations are extremely neat and accurate. The photo also shows the SWA termination and connections for the designed 06 circuit. This circuit is designated for the supply socket-outlet, serving the patch panel equipment.

Candidate demonstrates an excellent understanding of the installation requirements for the task. The candidate demonstrated an ability to sequence tasks logically, indicating a solid understanding of installing and commissioning the electrical and electronic equipment and systems as stated within the assignment brief without support.

Candidate follows correct and logical processes for the installation of all components, containment and equipment in this system.

The candidate demonstrates they can follow measurements accurately from an allocated work area, in line with their installation diagram.

The candidate demonstrated excellent accuracy when marking, cutting and installing materials.

Throughout the installation task the candidate showed accuracy, working within set tolerances.

All health and safety procedures were followed and adhered throughout this installation task.

Task 3 - Carry out maintenance

(Assessment themes: Health and safety, systems and components, reports and information, working with faults)

For task 3 candidates need to produce the following pieces of evidence:

- Carry out in-service inspection and testing on a range of 5 items of electrical and electronic equipment belonging to the client and provided by the assessor
- Documentation as required by IET CoP ISITEE

For illustration, the guided exemplification materials (GEM) for Task 3 contain examples of candidate evidence for the following assessment requirements only:

Documentation as required by IET CoP ISITEE

Note: For the purpose of this GSEM only 4 items are presented in the documentation


The following task 3 candidate assessment requirements have not been included as example candidate evidence for this version of the guided exemplification materials.

Assessor observation of inspection and testing

Photographic evidence required:

> Photograph of each item of equipment under test (any test within the range). This is to record the equipment under test and must align with the equipment register.

Task 3 - Documentation required by IET CoP ISITEE Inspection and testing record



Inspector Name:		C4.	16 Jenkin	Client:	c. b/			
(Note I) Organization:			& Guim	(Note 2)	T-LE	winor		
			2/2021	1				
Item		Note	Item I	Item 2	Item 3	Item 4		
Equipment ID	No.	3	01	07	03	04-		
Description		4	Keni	DaiLL	EX LEAD	4 CATEN		
Construction Cl	ass	.5	11	11	11.	1		
Type (S, IT, M,	P, H, F)	6	P	P	100	P.		
Location		7	office	office	office	office		
Frequency	Formal Visual Insp.	8	Worky	Weekay	Western	Meerin		
Combined Inspection & Test		9	1 year	14mm	7 464	7-4-4		
Make		10	KENWSTO	Densor.	MASTER	Grew.		
Model			0072	DWOT	SREU.	67		
Serial No.		1	12345.	678910	19W12.	7373		
Voltage (V) (if different from 230 V)		11	230√	230V	230/	2300		
Rating (watts or A)		12	10.5A	8 A	13A	13A		
Fuse (A)		. 13	134	134	134	13 1		
Condition of:	Socket-outlet	14						
(√ or ×)	Plug	14				/-		
	Flex	14	1	~				
	Body	14			/			
	Other (please state)	14	N/A	NIA	N/A	N/A		
Test Results	Continuity (Ω)	15(i)	0.1	0.14	0.12	0.1		
	Insulation Resistance (MΩ)	15(ii)	ممماذ	2000	>1000	>1000		
	Polarity ✓ or ×	15(iii)						
	Function ✓ or ×	15(iv)		/				
	Other (please state)	15(v)	N/A	N/A	N/A	W/1.		
Suitable for environment (Y or N)		16	У	У	Y	Y		
Comments		17						
Suitable for continued use (Y or N)		18	У	4	У	y.		
Initials		19	CI	CI	CJ	CJ.		



Note: (</) indicates pass, (*) indicates fail, (N/A) not applicable, (N/C) not checked

Candidate demonstrates a thorough understanding of the documentation requirements for the maintenance task. The inspection record is clear and detailed, with a new equipment register being compiled and supplied as part of the required paperwork. The manufacturer's instructions have clearly been used throughout the completion of the inspection record.

Full consideration and accurate use of technical language and terminology throughout the completed record and the documentation fully considers all materials and equipment, including safety and PPE.



The T Level is a qualification approved and managed by the Institute for Apprenticeships and Technical Education.

Copyright in this document belongs to, and is used under licence from, the Institute for Apprenticeships and Technical Education, © 2021. 'T-LEVELS' is a registered trademark of the Department for Education. 'T Level' is a registered trademark of the Institute for Apprenticeships and Technical Education. 'Institute for Apprenticeships & Technical Education' and logo are registered trademarks of the Institute for Apprenticeships and Technical Education.

We make every effort to ensure that the information contained in this publication is true and correct at the time of going to press. However, City & Guilds' products and services are subject to continuous development and improvement, and the right is reserved to change products and services from time to time. City & Guilds cannot accept responsibility for any loss or damage arising from the use of information in this publication.

The City & Guilds of London Institute. All rights reserved. City & Guilds is a trademark of the City & Guilds of London Institute, a charity established to promote education and training registered in England & Wales (312832) and Scotland (SC039576). City and Guilds Group Giltspur House, 5–6 Giltspur Street London EC1A 9DE

