

Institute for Apprenticeships & Technical Education

T Level Technical Qualification in Building Services Engineering for Construction

8710-353 Electrotechnical Engineering Grade Standard Exemplification Material Distinction - Summer 2023





Contents

Introduction	2
Grade descriptor	4
Task 1 Planning the installation	5
Task 2 Installation, commissioning and decommissioning	20
Task 3 Carrying out maintenance	32

Introduction

Summer 2023 Results

This document is aimed at providers and learners to help understand the standard that was required in the summer 2023 assessment series to achieve a distinction grade for the 8710-353 Electrotechnical Engineering Occupational Specialism (OS).

The aim of these materials is to provide examples of knowledge, skills and understanding that attested to distinction competence in summer 2023. It is important to note that in live assessments a candidate's performance is very likely to exhibit a spikey profile and standard of performance will vary across tasks.

 Grade
 Strongest performance

 Distinction
 ← This evidence

 Merit
 Pass

 Unclassified
 Weakest performance

The Occupational Specialism is graded Distinction, Merit, Pass or Unclassified.

The distinction grade boundary is based on a synoptic mark across all tasks. The materials in this Grade SEM are separated into two sections as described below. Materials are presented against a number of tasks from the assignment.

Task

This section details the tasks that the candidate has been asked to carry out. What needs to be submitted for marking and any additional evidence required including any photograph/video evidence. Candidate evidence that was or was not included in this Grade SEM has also been identified within this section.

In this Grade SEM there is candidate evidence from:

Task 1 Planning the installation Task 2 Installation, commissioning and decommissioning Task 3 Carrying out maintenance

Candidate evidence

This section includes exemplars of candidate work, photographs of the work in production (or completed) and practical observation records of the assessment completed by centre assessors. This was evidence that was captured as part of the assessment and then internally marked by the provider assessor.

The Occupation Specialism brief and tasks can be downloaded from here.

Important things to note:

- We discussed the approach to standard setting/maintaining with Ofqual and the other awarding organisations before awarding this year. We have agreed to take account of the newness of qualifications in how we award this year to recognise that students and teachers are less familiar with the assessments (Vocational and technical qualifications grading in 2023 – Ofqual blog), whilst also recognising the standards required for these qualifications.
- The evidence presented, as a whole, was sufficient to achieve the distinction grade. However, performance across the tasks may vary (i.e. some tasks completed to a higher/lower standard than distinction grade).

Grade descriptor

To achieve a distinction, a candidate will be able to:

Demonstrate an exemplary performance that fully meets the requirement of the brief and is able to enter the industry to begin to work in the occupational area.

Demonstrate exemplary technical skills for installing components that is in line with industry standards. They will also demonstrate relevant and comprehensive knowledge and understanding of principles and processes through the tasks completed.

Work safely and make informed and appropriate use of tools, materials and equipment within the environments that they are working in. They will competently and independently interpret information and apply the technical skills to practical tasks and procedures to an exemplary standard as recognised by industry, producing an excellent quality of work that meets acceptable tolerances, regulations and standards.

Confidently attempt some complex tasks and the level of performance meets an exemplary level.

Locate and identify faults, diagnose their causes and have a thorough understanding and the skills to be able to repair and rectify them.

Consistently use accurate industry terminology in both written and verbal contexts.

Task 1 Planning the installation

Assessment number (eg 1234-033)	8710-353
Assessment title	Electrotechnical Engineering Occupational Specialism
Candidate name	<first name=""> <surname></surname></first>
City & Guilds candidate No.	ABC1234
Provider name	<provider name=""></provider>
City & Guilds provider No.	999999a

Task(s)	1
Evidence title / description	 Completed design grid (Figure 3) and supporting calculations on a separate sheet Completed maximum demand and diversity schedule (Figure 4) Completed earth fault loop impedance schedule (Figure 5) Completed materials take-off sheet (Figure 6) Completed risk assessment (Figure 7)
Date submitted by candidate	DD/MM/YY

Task 1

Assessment themes:

•

- Health and safety
- Design and planning
 - Documentation
 - Technical information
 - Systems and components
 - o Installation
 - Decommissioning
- Reports and information
- a) Complete the design grid as in **Figure 3**. Any assumptions made in order to complete the design must be listed on a separate sheet with justifications.
- b) Complete the maximum demand and diversity schedule in **Figure 4** ensuring you give reasons and justifications for your application.
- c) Complete the earth fault loop impedance schedule in **Figure 5** based on the design drawings in **Figures 1 and 2**, and the installation design schedule in **Figure 3**.
- d) Complete the materials take off sheet in **Figure 6** based on the installation drawings in **Figures 1 and 2** and your design grid **Figure 3**.
- e) Complete the risk assessment in Figure 7 for the installation.

Additional evidence of candidate performance that must be captured for marking:

• Tutor/assessor's notes of the candidates referencing and research describing the methods used to reference or research information and how information was used or processed.

Candidate evidence

Figure 1 - Proposed shop layout



Figure 2 – Accommodation layout



8

T Level Technical Qualification in BSE for Construction: Electrotechnical Engineering Assessor Pack Summer 2023

Task 1 Figure 3 – Design Grid

Candidate name:

City & Guilds enrolment number:

Consumer unit located in cupboard in shop VOLTAGE DROP TO COMPLY WITH BS 7671		Nominal voltage (U/U₀) 230 V		Earthir	Earthing arrangement TN-C-S		External earth fault loop impedance (Ζ _e) 0.35 Ω	
Circuit	1	2	3	4 5		6	7	8
	first floor sockets	ground floor store/kitche	ground floor shop sockets west side	Radial-final ground floor shop sockets east side	Electric cooker 11.5 kW	Lighting ground floor sales area	Lighting ground floor store, kitchen/toilet	Lighting first floor accommodation and staircase
Number of outlets	15	6	9	7	1	9	5	
Type of wiring	70 °C thermoplasti c multi-core flat profile	70 °C thermoplasti c single- core non- sheathed	70 °C thermoplast ic single-core non-sheathed	70 °C thermoplasti c single- core non- sheathed	70 °C thermoplastic multi-core flat profile			70 °C thermoplast ic multi-core flat profile
Design current (I₅)	32 A	15 A	20 A	20 A	50 A	2.11 A	1.6 A	3.1 A
Type and nominal rating (I _n)	32 A B	20 A B	20 A C	20 A C	50 A B	6 A B	6 A C	6 A B
Length (metres)	68 m loop	26 m	25.95 m	26.9 m	7.1 m	26 m	18 m	47.75
Installation method	102	В	В	В	102	В	В	101
Ambient temperatur e °C	25 °C	25 °C	25 °C	25 °C	30 °C	30 °C	30 °C	30 °C

Rating factor Ambient air temp. C₄	1.03	1.03	1.03	1.03	1	1	1	1
Total circuits in group	1	2	2	2	1	1	1	1
Rating factor grouping C	1	0.8	0.8	0.8	1	1	1	1
Minimum current capacity (<l<sub>t)</l<sub>	31.1 A	24.27	24.27	24.2 7	60 . 96 A	6 A	6 A	6 A
mV/A/m	7.3	11	11	11	52.5	44	44	44
Actual voltage drop	7.94 v	4.29 v	5.709 v	5.891 v	0.994 v	2.41 v	1.267 v	6.51 v
Minimum conductor csa mm²	6 mm ²	4 mm ²	4 mm ²	4 mm ²	16 mm ²	1.5 mm ²	0.78 mm ²	1.5 mm ²

Task 1 Figure 4 – Maximum Demand and Diversity ScheduleCandidate name:City & Guilds enrolment number:

Circuit design current (A)	Diversity applied (% or factor)	Demand following diversity (A)	Reason for diversity application
1. 31.1 A	"I 1007. Of total Current demand up to A 10A; then in exser of to A 50% of consining current demand		Khis circuit is Accomposation So Not every socket will be being used simultainiously so diversity can be a palled here
2. 24.27 A		24.27 A	This is a kitchen/store room and the appliances change many times so diversity shouldn't be applied
3. 24.27 A	No diversity applied	20 A	This is a large store open area that will use all available sockets for long periods of time – no diversity
4. 24.27 A	No diversity applied	24.27 A	This is the same as circuit 4. Diversity should not be applied.

5. 60.86 A	"10 A + 30%. of exsent Current demand + SA if soche & a Helderd"	25.26 A	A rooker is wever used a its full use for extended periods of aime 30 diversity is clique bly.
6. 6 A	90 % of total current demand	5.4 A	Whilst stores use lights for long periods at night they aren't occupied so lights are turned off.
7. 6 A	90 % of total current demand	5.4 A	Stores don't use lights after closing so diversity can be applied.
8. 6 A	66% of total current demand	3.96 A	Stol during working haves accompositions don't us hights and directily 1-m se spolled
Maximum demand (A)	182.77 A	Maximum demand after diversity (A)	133.38 A
Maximum demand (kVA)	0.183 KA	Maximum demand after diversity (kVA)	0.133 A

Task 1 Figure 5 – Earth Fault Loop Impedance ScheduleCandidate name:City & Guilds enrolment number:

Circuit	Protective device	Circuit length	R₁+R₂ at operating temperatures	Zs	Maximum permitted Z₅ (BS7671)	Calculations/comments
1. Ring final circuit first floor socket- outlets	32 A B Type BS EN 61009	68 m loop	10.49	1.2 Ω	1.37	Comprises <s 1-znis<="" td=""></s>
						1-55 1400 1-37 s
	20 A C Type BS EN 61009	26.9 m	16.71	0.88 Ω	1.09 Ω	Compriss less chan
						1.09.2.

Task 1 - Figure 6 - Materials Take off Sheet (relating to Figures 1, 2 and **3**) *This sheet may be reproduced as many times as necessary*

Candidate name:

City & Guilds enrolment number:

Symbol	Description	Quantity				
	Consumer unit	1				
	2 x 35 W LED Batton luminaire	5				
	9					
	10 W recess lumaire LED	9				
\times	40 W light point	9				
	1 gang light switch					

Sa	Multi gang light switch	1
5	Two way light switch	3
01	Cord operated light switch	1
2/2	Z gang 13 A switched socket outlet	35
6	1 gange 13A in Smitches Sochet Sution to findge frenzer	1

Task 1 - Risk Assessment

This risk assessment form may be modified by adding items only

Candidate name:

City & Guilds enrolment number:

Activit Locatio	y: Practical assessment on:		Date: Position: Employee				
	RTY (S): Degree of harm which r Injury 2 Major Injury 3 Fa	may be caused (inclu tality	uding numbers affecte	ed)	RISK R <i>I</i> x Likelir		R): Severity
LIKELI 1 Rem	HOOD (L): Probability that eve ote 2 Possible 3 Lil				1-2 Low 3-5 Med 6-9 High	ium	
ltem No:	Activity	Hazard	Persons at Risk	Existing Controls (Mitigation)	S 1-3	L 1-3	RR
1	Walking around workshop	Slips, trips, falls	Worker/Public	Tidy up, good housekeeping, sections for cutting etc	1	3	3
2	low benging Sochet boyos	Hitting head	Worker	Hard hat, be vigilant	1	2	2
3	Clipping coble Direke	Hitting hand with hammer	Worker	Globes, training, competancy	1	1	1
4	Carrying dado trunking	Dropping object on foot	Worker	Steel toe cap boots	1	1	1

Practical Observation (PO) Form (Task 1)

8710-33 T Level Technical Qualification in Building Services Engineering for Construction

8710-353 Electrotechnical Engineering (Summer 2023)

Candidate name	<first name=""> <surname></surname></first>
City & Guilds candidate No.	ABC1234
Date	24/04/2023

Provider name	<provider name=""></provider>
City & Guilds Provider No.	999999a

Task 1 assessment themes:

•

- Health and safety
- Design and planning
 - Documentation
 - Technical information
 - Systems and components
 - o Installation
 - \circ Decommissioning
- Reports and information

Record observation notes below to inform internal marking and external moderation. Notes must be detailed, accurate and differentiating which use terminology from the mark grid along with specific examples observed. Notes must identify areas of strength and weakness, distinguish between different qualities of performance and to facilitate accurate allocation of marks once all evidence has been submitted.

Assessment Themes	Assessor observation notes
Health and safety • Risk assessment • Risk mitigation • Harm and probability factors • Adherence to health and safety	Risk mitigation methods are detailed and have been clearly identified for all potential risks. Potential for harm and probability factors have been identified throughout. Consideration given to potential for harm and probability factors. Health and safety is followed during preparation and throughout tasks and all work completed safely

Design and planning (documentation) • Quality of planning and design • Quality of documentation • Accuracy • Symbols, abbreviations and terminology	General planning and design work undertaken is comprehensive with a high attention to detail. Efficient use of research materials and a good understanding of technical documents. Links made between drawing and practical situations with excellent assumptions made where information lacked. Provides a high level of accuracy in reports and written detail consistently ensuring and checking for accuracies with reference made to manufacturers' instructions and regulations. Terminology is used generally correctly throughout.
Adherence to industry standards Design and planning	Links all areas of the assessment of general characteristics to the
 (technical information) Assessment of general characteristics Link to installation drawings Calculations Understanding of BS 7671 Selection of luminaires Identification, descriptions and quantities of items Diagrams Calculations Calculations 	installation and makes informed decisions as to relevance and impact. Calculations accurate and well researched showing good understanding of technical information in BS 7671 as well as confident navigation. Accurate calculations to determine luminaire output but selection may not consider all factors such as aesthetics, practical installation and suitability. All items identified using provided resources with good technical descriptions and accurate quantities. Able to understand all aspects of drawing and understands the associated accessories needed rather than the basic accessories shown on drawings. Diagrams accurate and meets the installation specification. Calculations are accurate but there are gaps in workings that does not clearly show that all factors have been considered. Some units are not specified. Presentation of work is mostly clear.
Systems and components (installation) Adherence to industry standards Sequencing Component selection Installation skills Selection and use of tools Reference to / follows manufacturer's instructions Measurement Adherence to design spec	Installation to industry standards and is completed in a timely manner. Component selection appropriate and clearly links to the quality of finished installation. Confidence and competence displayed in the installation process with levels of skills shown in the quality of the finished installation. Use of tools is excellent resulting in a near high-quality installation. Candidate follows manufacturer's instructions at most stages of the installation. Measurement wiring and associated components is to a sound standard with clear attempts to meet industry levels, resulting in an install that has few errors from the proposed installation plan.

Systems and components (decommissioning) • Sequencing • Damage to parts • Removal techniques • Designation and categorisation for disposal	Consideration of implications of sequence for dismantling, minimising damage to parts that could be recycled. Use of removal techniques to salvage as much materials as possible for recycling. All removed materials and equipment suitably designated and categorised for disposal as required.
Reports and information • Terminology • Explanations / reasoning • Accuracy of certification and schedules	Consistently use industry terminology appropriately in both written and verbal contexts. Certification and schedules completed with minimal but accurate detail in all aspects.

Any other aspects

All tasks were to a good standard. Clipping of PVC/PVC cable was good, but not clipped to batten as shown in the drawing.

Internal assessor signature	Date
	28/04/2023

If completing electronically, double click next to the 'X' to add an electronic signature once the record is **finalised**.

Task 2 Installation, commissioning and decommissioning

Assessment number (eg 1234-033)	8710-353
Assessment title	Electrotechnical Engineering Occupational Specialism
Candidate name	<first name=""> <surname></surname></first>
City & Guilds candidate No.	ABC1234
Provider name	<provider name=""></provider>
City & Guilds provider No.	999999a

Task(s)	2
Evidence title / description	Completed Electrical Installation Certificate and associated documents.
Date submitted by candidate	DD/MM/YY

Task 2

Assessment themes:

- Health and safety
 - Systems and components
 - o Documentation
 - Technical information
- Reports and information
- Inspecting and testing of systems and components
- Handover and communication

a) Installation

Candidates must:

• Complete the installation in accordance with the drawing (**Figure 8**) and to the dimensions agreed with your tutor/assessor.

All cables and wiring systems **must** be terminated and installed in accordance with BS 7671. All terminations, joints and couplings must be mechanically secure and electrically continuous where applicable. Wastage must be minimised as far as possible.

b) Inspection, testing and commissioning

Candidates must:

- Carry out safe isolation to the distribution board prior to commencement of the installation initial verification.
- Carry out an inspection and complete the inspection schedule for initial verification.
- Carry out the full range of applicable tests, in the correct sequence, to the completed installation. Permission must be obtained from the tutor/assessor before proceeding with any tests involving switching on the supply.
- Use instruments safely and in accordance with manufacturer's information and HSE GS38.
- Complete a schedule of test results for the results obtained.
- Compare results with BS 7671 and design criteria.

safe prior to the circuits being energised and tested for function.

- Complete the Electrical Installation Certificate for this installation.
- Carry out a handover of the installation with the tutor/assessor as the client.

All work must be to current standards and carried out in accordance with all health and safety requirements. Any unsafe actions will result in termination of this assessment. The tutor/assessor must be satisfied that the work complies with BS 7671 and is electrically

- Ensure the workspace is made good, including filling, sanding and painting any holes or damage to the building fabric.
- Following dismantling, consideration must be given to sustainability and recycling.

c) Decommissioning

Once the installation has been completed, checked and verified by the client (tutor/assessor) candidates must

- Decommission in a safe manner ensuring safe isolation.
- Ensure the workspace is made good, including filling, sanding and painting any holes or damage to the building fabric. This does not include the holes made in the plasterboard.
- Undertake a professional discussion with the client (tutor/assessor) on the correct methods for recycling or disposing of waste.

Additional evidence of candidate performance that must be captured for marking:

- Tutor/assessor feedback on performance
- Photographs showing the installed work clearly (not the candidate) taken at the following intervals:
 - Installation:
 - 2 hours
 - 4 hours
 - 6 hours
 - 10 hours and on completion
 - Commissioning:
 - During a test for Z_s for the distribution circuit (Z_{db}) at DB

• Decommissioning:

• On completion

Installed components are to be installed to required standards, with photographic evidence confirming accuracies and attention to details.

Candidate evidence

Completed Electrical Installation Certificate

	Certificate No.:
DETAILS OF THE CLIENT	
INSTALLATION ADDRESS	
DESCRIPTION AND EXTENT OF THE INSTALLATION Description of installation: flackical Assassment T3 c:1d	New Installation
Extent of installation covered by this Certificate:	Addition to an existing installation
(Use continuation sheet If necessary) See cont	Alteration to an existing installation
FOR DESIGN	
We, being the segson(s) responsible for the design of the electrical installation (as indicated of which are described above, having exercised reasonable skill and care when carrying out that the design work for which the have been responsible is to the best of mylour knowledge	the design, hereby CERTIFY and belief in accordance with
We, being the seconds) responsible for the design of the electrical installation (as indicated of which are described above, having exarcised reasonable skill and care when carrying out that the design work for with the law have been responsible is to the best of my/our knowledge BS 7671:2018, amended to (date) except for the departures, if any, detailed as	the design, hereby CERTIFY and belief in accordance with
We, being the seconds) responsible for the design of the electrical installation (as indicated of which are described by the have been responsible is to the best of my/our knowledge that the design work for which have been responsible is to the best of my/our knowledge BB 7671:2018, amended to (date) except for the departures, if any, detailed as Details of departures from BS 7671 (Regulations 129.3, 133.1.3 and 133.5):	the design, hereby CERTIFY and belief in accordance with follows:
IWe, being the section(s) responsible for the design of the electrical installation (as indicated of which are describer above, having exercised reasonable skill and care when carrying out that the design work for which lave have been responsible is to the best of my/our knowledge BS 7671:2018, amended to	the design, hereby CERTIFY and belief in accordance with follows: ament(s) must be attached to this Certificate.
We, being the seconds) responsible for the design of the electrical installation (as indicated of which are describer above, having exercised reasonable skill and care when carrying out that the design work for which the have been responsible is to the best of my/our knowledge BS 7671:2018, amended to	the design, hereby CERTIFY and belief in accordance with follows: ament(s) must be attached to this Certificate. Risk assessment attached
We, being the serson(s) responsible for the design of the electrical installation (as indicated of which are described above, having exercised reasonable skill and care when carrying out that the design work for which there have been responsible is to the best of mylour knowledge BS 7671:2016, amended to	the design, hereby CERTIFY and belief in accordance with follows: sment(s) must be attached to this Certificate. Risk assessment attached the subject of the Certificate.
FOR DESIGN I/We, being The seconds responsible for the design of the electrical installation (as indicated of which are described above, having exercised reasonable skill and care when carrying out that the design work for writer-back have been responsible is to the best of myfour knowledge BS 7671:2018, amended to	the design, hereby CERTIFY and belief in accordance with follows: ament(s) must be attached to this Certificate. Risk assessment attached Risk assessment attached the subject of the Certificate. e is mutual responsibility or the design)

FOR CONSTRUCTION I, being the person responsible for the construction of the electrical instaliation (as indicated by my signature below), particulars of which are described above, having exercised reasonable skill and care when carrying out the construction hereby CERTIFY that the construction work for which I have been responsible is to the best of my knowledge and belief in accordance with BS 7671:2018, amended to Astronomic (date) except for the departures, if any, detailed as follows:
Details of departures from BS 7671 (Regulations 120.3 and 133.5):
The extent of liability of the signatory or signatories is limited to the work described above as the subject of this Certificate. For CONSTRUCTION of the Installation:
FOR INSPECTION AND TESTING I, being the parson responsible for the inspection & testing of the electrical installation (as indicated by my signature below), particulars of which are described above, having exarcised reasonable skill and care when carrying out the inspection & testing hereby CERTIFY that the work for which I have been responsible is to the best of my knowledge and belief in accordance with BS 7671:2018, amended to
Details of departures from BS 7671 (Regulations 120.3 and 133.5):
The extent of liability of the signatory or signatories is limited to the work described above as the subject of this Certificate. For INSPECTION AND TESTING of the Installation: ASSESSMENT ASYMPTOTIC APITALS: A subject of this Certificate. Signature: Assessment Asymptotic Apital Signature: Asymptotic A
NEXT INSPECTION I/We, the designer(s), recommend that this installation is further inspected and tested after an interval of not more than

ARTICULAR	S OF SIGNATOR	IES TO TI	HE ELECTI	RICAL INSTA	LLATION	CERTIFICA	TE		/
iesigner (No 1									
								Tel No:	
esigner (No 2	2) Name:				Compe	any			
fapplicable)	Address:								
				1				. Tel No:	
onstructor									
								. Tel No:	
nspector	Name:				Compa	any:			
								Tel Mar	
	ACTERISTICS					08;		. Tel No:	
Earthing	1					d Burnelly Barrow		Russhy David	anthun Dauda
rrangements	Number and	Type of Liv				f Supply Para		Supply Prot	
v-c ⊡ v-s ⊡	AC 🗹 1-phase, 2-wire		DC 2-wire	Nomia Nomia	nal voltege,	U/U/ ^{K0}	3.0	V BS (EN)	C
⊷ ⊷c-s 📈	2-phase, 3-wire		3-wire	Prosp	ective fault	current, 1,000.	-39.9	kA Rated current .	
· 📋	3-phase, 3-wire	=	Other	Exter	nal earth far	uit Z ^{ay} Q			
	3-phase, 4-wire					2) by enquiry or by s		×	
	Confirmation of				i) by evelous (th ch sudney or ph y	neastronining		
	oF INSTALLAT				TIELCATE				
Means of I					M	aximum Dem	and		
stributor's facilit	-	Maximur	m demand (lo	oad)	63		Amps (Dek	ete as appropriate)	
tallation earth (Tune (e.c	n methel ten	Details of	' Installatio	n Earth Electr	ode (where	applicable)	
		Location							
ain Brotecth	e Conductors	Electrode	e resistance	to Earth					
an Protocuv									
withing conducts	vr Motori	int (· ./	055		2,5	mm2	Connection / configuil	www.
-			<u> </u>			2: 5		Connection / continuit	
ain protective	Materi					<u>, 5</u> /O		Connection / continuit Connection / continuit	
ain protective nding conducto	Matari	iel	<u>s</u>	C\$8		10	mm²	Connection / continuit	ty vertfied
aln protective inding conducto water installation	Matari	jal	ation pipes [To oil ins	stalistion pip	10		Connection / continuit	
ain protective inding conducto water Installation other Spec	Materi Ins	iel	ation pipes [To oil ins	stalistion pip	10	mm²	Connection / continuit	ty vertfied
ain switch / \$	Materi on pipes	gas installs cult-breal	ation pipes [ker / RCD	To oil Ins	stallation pip	/О рев 🗌 То :	structural st	Connection / continuit	ty vertfied
ain protective inding conductor water installati- other Special cation	Materi on pipes To sty	al	ation pipes [ker / RCD Current r Fuse / dr	To oil Ins	stalistion pip		structural so If RCD n RCD Typ	Connection / continuit	protection
ain protective inding conductor water Installati- other Special cation Spe	Materi on pipes To sty	gas Installe cult-breal	ation pipes [ker / RCD Current r Fuse / dr	To oli ins	stalistion pip		structural st If RCD n RCD Type Rated res	Connection / continuit eel To lightning main switch	ty vertified [protection [
In protective inding conductor water Installation other Special cation Special cation Conductor (EN)	Materi on pipes To sty	gas Installe cult-breal	ation pipes [ker / RCD Current r Fuse / dr	To oil Ins	stalistion pip		structural so If RCD n RCD Type Rated ree Rated ree	Connection / continuit	protection [transfer (a)
In protective inding conductor water Installation other Special cation Special cation Conductor (EN)	Materi on pipes To sty	gas Installe cult-breal	ation pipes [ker / RCD Current r Fuse / dr	To oil Ins	stalistion pip		If RCD m RCD Type Rated ree Rated ree Rated ree	Connection / continuit eel To lightning main switch	protection [transferred transferred trans
In protective ading conductor water Installant other Speed all switch / s cation	Materi on pipes To switch-fuse / Cir	gas Installe cult-breal	ation pipes [ker / RCD Current r Fuse / dr	To oil Ins To oil Ins rating	stalistion pip		If RCD m RCD Type Rated ree Rated ree Rated ree	Connection / continuit eel To lightning nain switch delay	ty verified [
In protective ading conductor water Installation otherSpectral cation cation cation cation cation cation cation cation cation cation cation cation cation cation cation cation cation cation cation cation cat	Materi on pipes To switch-fuse / Cir	gas installe cult-breal	ation pipes [ker / RCD Current r Fuse / dr	To oil Ins	stalistion pip		if RCD m RCD Type Rated ree Rated inf	Connection / continuit eel To lightning nain switch delay	protection [transferred transferred trans
In protective ding conductor water Installation other Speed all switch / Speed (EN) of poles	Materi on pipes To atty witch-fuse / Cir witch-fuse / Cir spections Descript on of consumer's in	ges Installe cult-break	ation pipes [ker / RCD Current I Fuse / di Voltage I	To oil Instating	etting		If RCD m RCD Type Rated ree Rated ree Rated ree Rated ree Rated ree Rated ree Rated ree Rated ree	Connection / continuit eel To lightning nain ewitch delay	ty verified [protection [t (r _{an})
In protective ading conductor water Installation othersecond all switch / so cationsecond t (EN)second t (EN)	Materi on pipes To alty witch-fuse / Cir witch-fuse / Cir spections Descript	ges Installe	ation pipes [ker / RCD Current I Fuse / di Voltage I	To oll Ins ating	ettilletion pip ettilletion pip etting etting etting	10 006 To 10 10 10 10 10 10 10 10 10 10	If RCD m RCD Type Rated res Rated int Description and	Connection / continuit eel To lightning nain ewitch delay	ty verified [protection [t (r _{an})
in protective inding conducts water Installation other Special cation	Materi on pipes To atty witch-fuse / Cir witch-fuse / Cir spections Descript on of consumer's in	ial	ation pipes [ker / RCD Current i Fuse / di Voltage i	To oil Instating	Item No.	Circuits (Diet Isolation and Current-using	If RCD m RCD Type Rated ree Rated Jim Describution and switching g equipment	Connection / continuit eei To lightning nain ewitch delay coperating time ription Final)	ty verified [protection [t (r _{an})
ain protective noting conductor water Installation conter Special cation Special	Materi on pipes To ity witch-fuse / Cir witch-fuse / Cir	gas Installe cult-breat	ation pipes [ker / RCD Current i Fuse / di Voltage i Notage i	To oil Instating	Item No. 9.0	Circuits (Dist	If RCD m RCD Type Rated ree Rated Jim Describution and switching g equipment	Connection / continuit eei To lightning nain ewitch delay coperating time ription Final)	ty verified [protection [t (r _{an})
ain protective inding conducts water Installant inding conducts water Installant ain switch / s cation	Materi on pipes To ity To ity	gas Installe cult-breat	ation pipes [ker / RCD Current i Fuse / di Voltage i Notage i	To oil Instating	Item No. 8.0 9.0 10.0	Circuits (Diet Isolation and Current-using (permanently Identification	If RCD m RCD Type Rated rea Rated in Surect Describution and switching g equipment connected and notices	Connection / continuit eel To lightning nain switch delay delay operating time ription Final)	v verified [
in protective noting conducts water Installant conterseat all switch / s cationc cation _	Materi on pipes To ify invitch-fuse / Cir witch-fuse / Cir invitch-fuse / Cir i	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Notage i	CSA To oil Ins rating ovice rating ovice rating ovice rating ovice rating Outcome	Item No. 8.0 9.0 10.0 11.0 12.0	Circuits (Dist isolation and Current-using (permanently Identification Location(s) of	If RCD m RCD Type Rated rea Rated rea Rated real Rated Rated real Rated real	Connection / continuit eel To lightning nain switch delay operating time ription Final)	ty verified [protection [t (r _{an})
in protective noting conductor water Installant other Speed all switch / 3 cation	Materi ns on pipes [] To ity ity	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Notage i	To oil Instating	Item No. 8.0 9.0 10.0 11.0 13.0	Circuits (Dist isolation and Current-using (permanently Identification Location(s) o Other specia	If RCD m RCD Typ Rated reg Rated reg	Connection / continuit eel To lightning nain switch delay operating time ription Final)	v verified [
in protective noting conductor water Installant other Speed all switch / 3 cation	Materi and pipes To tify To tify Witch-fuse / Cir witch-fuse / Cir awitch-fuse / Cir aminipaction appections Descript prof consumer's in inspection only) or switched alterna- we measure: the Disconnection of rotection we measures other all protection	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Notage i	CSA To oil Ins rating ovice rating ovice rating ovice rating ovice rating Outcome	Item No. 8.0 9.0 10.0 11.0 12.0	Circuits (Dist Isolation and Current-using (permanently Identification Location(s) of Other specia Prosumer's I	If RCD n RCD Type Rated real Rated real Switching equipment connected and notices containing a i installation ow voltage of	Connection / continuit eel To lightning nain switch delay operating time ription Final)	verified protection [t (T _{ac})
ain protective noting conductor water installation other is speed all switch / signature (CRN) (CRN) (Condition (Condition) (C	Materi ns on pipes [] To ity ity ity ity ity ity ity ity	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Voltage i Notage i	CSA To oil Ins ating (1 ovice rating or 1 rating 2 Outcome 7/N/A N/A N/A N/A V N/A	Item No. 8.0 9.0 10.0 11.0 12.0 13.0 14.0	Circuits (Dist Isolation and Current-using (permanuly Identification Location(s) of Other specia Prosumer's in installation(s)	If RCD m RCD Typ Rated res Rated in RCD Typ Rated res Rated in Second Desc ribution and switching equipment connected and noticed containing a i Installation ow voltage (Connection / continuit eel To lightning nain switch delay	v verified [
In protective Inding conductor water Installation other Speed cation Switch / 3 (EN) of poles hedule of In 1 No. Condition Parallel Parallel Protecti Addition Distribut	Materi and pipes To tify To tify Witch-fuse / Cir witch-fuse / Cir awitch-fuse / Cir aminipaction appections Descript prof consumer's in inspection only) or switched alterna- we measure: the Disconnection of rotection we measures other all protection	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Voltage i Notage i	CSA To oil Ins ating (1 ovice rating or 1 rating 2 Outcome 7/N/A N/A N/A N/A V N/A	Item No. 8.0 9.0 10.0 11.0 12.0 13.0 14.0	Circuits (Dist Isolation and Current-using (permanuly Identification Location(s) of Other specia Prosumer's in installation(s)	If RCD m RCD Typ Rated res Rated in RCD Typ Rated res Rated in Second Desc ribution and switching equipment connected and noticed containing a i Installation ow voltage (Connection / continuit eel To lightning nain switch delay	verified protection [t (T _{ac})
in protective noting conductor water Installation other Speed all switch / 3 cation	Materi ns on pipes To ity ity	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Voltage i Notage i DS)	CSA To oil Ins ating wice rating or ating Outcome //N/A N/A N/A N/A V N/A	Item No. 8.0 9.0 10.0 11.0 12.0 13.0 14.0 cition or al	Circuits (Dist Isolation and Current-using (permanently Identification Location(s) of Other specia Prosumer's li installation(s)	If RCD m RCD Typ Rated res Rated res Rated res Rated res Rated res resurces Description and switching equipment connected and notices containing a i installation ow voitage o Regulation	Connection / continuit eel To lightning nain switch delay	verified protection [t (T _{ab})
in protective noting conductor water Installation other Speed all switch / 3 cation	Materi ns on pipes To ity ity	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Voltage i Notage i DS)	CSA To oil Ins ating wice rating or ating Outcome //N/A N/A N/A N/A V N/A	Item No. 8.0 9.0 10.0 11.0 12.0 13.0 14.0 cition or al	Circuits (Dist Isolation and Current-using (permanently Identification Location(s) of Other specia Prosumer's li installation(s)	If RCD m RCD Typ Rated res Rated res Rated res Rated res Rated res resurces Description and switching equipment connected and notices containing a i installation ow voitage o Regulation	Connection / continuit eel To lightning nain switch id constraints current id constraints current id constraints current id constraints current id constraints current id constraints current id constraints current is constraints bath or shower is or locations electrical 644.1.2):	verified protection [t (T _{ab})
ain protective noting conductor water installation other is speed all switch / signature (CRN) (CRN) (Condition (Condition) (C	Materi ns on pipes To ity ity	al	ation pipes [ker / RCD Current i Fuse / di Voltage i Voltage i Notage i DS)	CSA To oil Ins ating wice rating or ating Outcome //N/A N/A N/A N/A V N/A	Item No. 8.0 9.0 10.0 11.0 12.0 13.0 14.0 cition or al	Circuits (Dist Isolation and Current-using (permanently Identification Location(s) of Other specia Prosumer's li installation(s)	If RCD m RCD Typ Rated res Rated res Rated res Rated res Rated res resurces Description and switching equipment connected and notices containing a i installation ow voitage o Regulation	Connection / continuit eel To lightning nain switch id constraints current id constraints current id constraints current id constraints current id constraints current id constraints current id constraints current is constraints bath or shower is or locations electrical 644.1.2):	verified protection [t (T _{ab})

GENE	RIC SCHE	DULE OF CIRCL	JIT DETAILS										(Certificate/Rep	ort No.	1	
DB re Distrib																	
-							CIRCUI	DETAIL	s								
					C	onductor	details		Over	current p	protective	device	1		RCD		
						7	Numb	er & size					(C)				
Circuit number	2	Circuit description		Type of wiring	A Reference method#	n Number of points served	a Live (mm²)	cpc (mm²)	BS (EN)	Type	c Rating (A)	± Bresking capacity (kA)	$\mathcal{R}^{2}_{a}\left(\Omega\right)^{k}$ (Ω^{jk}	13 (EN)	t Type	ti I _{de} (mA)	Rating (A)
1	Ring Fi	a= (A	C	4	2.5	1-5	60898	ß	32	6	(-)	61008	NIA	30	80
2	Actor			É	B	4	2.5	2.5	60898	B	20	6	1-75	61008	NIA	30	60
à	space			E	B	(1-5	1.5	60 89 8	0	6	6	5:07	8 100 3	NIA	30	80
						COD	ES FOR 1	YPES OF V	VIRING			-	-		1		<u> </u>
	A	в	С	1	D			E	F			G		н		0	
	oplastic insulated/ aathed cables	Thermoplestic cables in metallic conduit	Thermoplastic cables in non-metal%c conduit		ermoplastic metallic tru			lestic cables in tellic trunking	Thermopie SWA cab			rmosetting VA cables		vlineral insulated cab	ice	Other - pice	io stato

SPD Type. Where a combined T1 + T2 or T2 + T3 device is installed, indicate by ticking both Type boxes.
 Where a T3 SPD is installed to protect sensitive equipment, enter details in 'Remerica', column 31, of the Schedulo of Tost Results. (See Section 534 of BS 7671:2018+A2:2022.)
 See Table 4A2 of Appandix 4 of BS 7871:2018+A2:2022.
 Where the madrum permittide auth fault toop impedance value stated in column 12 is taken from a source other than the tabulated values given in Chapter 41 of BS 7671:2018+A2:2022, state the source of the date in the
 accomprise cell for the circuit in the Remerics', column 31, of the Schedule of Test Results.

ENE	RIC SU	HEDU	LEOF	TEST	RESUL	.15		3	98					Certificate/Report No.:
	med:	Correct p	olarity	Z _e [] Phase confirme	e sequen	∞ □		_Ω [0.39			- kA	Details of test instruments used (serial and/or asset numbers) Multifunction: 5[43] 102158681 Continuity: 5[43] 102458681 Insulation resistance: 4[N] 10258681 Earth fault loop impedance: 5[N] 10258681 RCD: 5[A] 10258681 Earth electrode resistance: 5[N] 10258681
_		_					757 57 - 28		TE	ST RES	1		1	
		Co	ontinuity (α)		Insula	tion resis	tance		Ζ, (Ω)	R	CD	AFDD	
	Rin	g final cir	cuit	(R, + R	ς) or R ₂					pe	e (ms)"	tion	operation	Remarks
Circuit number	해 r ₁ (line) (D)	ة r, (neutral)	k r ₂ (cpc)	ч (R, + R ₂)	22 ^{22°}	8 Test voltage (V)	¥ Live - Live (MΩ)	S Live - Earth (MD)	8 Polarity ^e	2 Meximum measured	& Disconnection time (ms)"	& Test button operation	8 Menuel test button operation	Include details of circuits and/or installed equipment vulnerable to damage when testing (continue on a separate sheet if necessary)
	0-48	2.00	8-24	0.47	NIA	Baav	79.44	3440	V	3.52	28	1	NA	
_	ACIA	NIA	NIA	0.14	NIA	500	TARF	7141	V	9.4	28	V	NIA	
2	N IA \$	NIA	NIA	5-73	NIA	500	7994	>144	V	0-74	2.8	-	NIA	Spare
-														
					-									
iested	l by name ture:	(Capital	s):	6		7		Date:	_2,	6.4.	23			

¶ Not all SPDs have visible functionality indication. # An X², denoting incorrect polarity, cannot be entered on to this schedule when issued with an Electrical Installation Cortificate. ** RCD effectiveness is verified using an alternating current test at rated residual operating current (i_{tab}).





Practical Observation (PO) Form (Task 2)

8710-33 T Level Technical Qualification in Building Services Engineering for Construction

8710-353 Electrotechnical Engineering (Summer 2023)

Candidate name	<pre><first name=""> <surname></surname></first></pre>
City & Guilds candidate No.	ABC1234
Date	25/04/2023

Provider name	<provider name=""></provider>
City & Guilds Provider No.	999999a

Task 2 assessment themes:

- Health and safety
- Systems and components
 - Documentation
 - Technical information
- Reports and information
- Inspecting and testing of systems and components
- Handover and communication

Record observation notes below to inform internal marking and external moderation. Notes must be detailed, accurate and differentiating which use terminology from the mark grid along with specific examples observed. Notes must identify areas of strength and weakness, distinguish between different qualities of performance and to facilitate accurate allocation of marks once all evidence has been submitted.

Assessment theme	Assessor observation notes
Health and safety • Risk assessment • Risk mitigation • Harm and probability factors • Adherence to health and safety	Risk mitigation methods identified for some of the potential risks, but not all. Consideration given to potential for harm and probability factors. Health and safety is followed during preparation and throughout tasks and all work completed safely
Systems and components (Installation) • Installation procedure • Appropriate component selection • Confidence and competence	Installation to industry standards and is completed in a timely manner. Component selection appropriate and clearly links to the quality of finished installation. Confidence and competence displayed in the installation process with levels of skills shown in the quality of the finished installation. Use of tools is excellent resulting in a near high-quality installation. Candidate follows manufacturer's instructions at most stages of the installation.

displayed in installation process • Ability to use appropriate tools • Following manufacturer's instructions	Measurement wiring and associated components is to a sound standard with clear attempts to meet industry levels, resulting in an install that has few errors from the proposed installation plan.
Systems and components (Decommissioning) • Consideration of implications of sequence • Salvage of materials for recycling • Designation and categorisation for disposal	Consideration of implications of sequence for dismantling, minimising damage to parts that could be recycled. Use of removal techniques to salvage as much materials as possible for recycling. All removed materials and equipment suitably designated and categorised for disposal as required.
Reports and information • Technical	Consistently use industry terminology appropriately in both written and verbal contexts. Certification and schedules completed with minimal but accurate detail in all aspects.
Inspecting and	Demonstrates relevant and comprehensive knowledge and understanding of Electrical principles and processes. Can competently and independently interpret information. Can demonstrate excellent planning, assess risk and follow safe working methods. All safety aspects considered, and correct safe isolation procedures undertaken before dismantling commences. Demonstrates good, consistent skills, which meets industry standards. Work is well planned following a logical sequence and is completed in a timely manner. Works within tolerances. Complex situations are attempted well and mostly effectively. Regularly confirms outcomes with use of good supporting reference materials. Good links between knowledge and practice giving consideration to aspects such as the number of cores required. Follows correct testing sequence with no prompting.

 Links between knowledge and practical Tolerances / quality Use of tools and plant Testing sequence 	
Handover and communication • Detail / explanations • Consideration of client perspective • Communication style • Customer care skills	Handover considered and well organised/ structured and all elements explained. Consideration of client perspective and requirements, confirmation of understanding sought.

Any other aspects

Good quality of work throughout, showing confidence and ability.

Internal assessor signature	Date
	28/04/2023

If completing electronically, double click next to the 'X' to add an electronic signature once the record is **finalised**.

Task 3 Carrying out maintenance

Assessment number (eg 1234-033)	8710-353
Assessment title	Electrotechnical Engineering Occupational specialism
Candidate name	<first name=""> <surname></surname></first>
City & Guilds candidate No.	ABC1234
Provider name	<provider name=""></provider>
City & Guilds provider No.	999999a

Task(s)	3
Evidence title / description	Six completed report cards.
Date submitted by candidate	DD/MM/YY

Task 3

Assessment themes:

- Health and safety
 - Systems and components
 - Documentation
 - Technical information
- Reports and information
- Handover and communication
- Working with faults

Candidates must carry out the following for a **minimum** of **six** faults. All work must be undertaken with the installation fully isolated.

Fault tables for this task can be found in the Assessor Guide to Test Rigs document. This document must not be shared with candidates.

For each fault, candidates must:

- Select a job card from the range offered by the tutor/assessor
- Copy the job card reference number onto the blank report sheet in Figure 9
- Identify from the range of equipment given, necessary items that will be required in order to prepare and diagnose the fault description provided
- Carry out checks to test equipment prior to using it
- Locate the fault, using a logical process
- Complete the report sheet to evidence the following:
 - Description of work done to find the fault
 - Tests carried out to locate the fault (if any)
 - The nature of the fault
 - $\circ~$ Brief description of actions required, including materials and time required to rectify the fault
 - Further actions required to ensure rectification is suitable.

All work **must** be to current standards and carried out in accordance with **all** health and safety requirements. Any unsafe actions will result in termination of assessment.

Additional evidence of candidate performance that must be captured for marking:

- Tutor/assessor feedback on performance of diagnostic techniques
- Tutor/assessor observations.

Candidate evidence

Figure 9 - Fault Report Sheet

Task 3 Fault Report Sheet Job card reference number: WK9	
Description of work done/ tests	s carried out to locate fault (if any)
Continuity test	(END to End), U: Soul Inspection
Earta is corre Nectral 15 Corre	ect reit
Break in the We reading.	Line Conductor leading to
The nature of the fault	
After testing be	was a continuity, lesting
Swife has fuere a	was a continuity, testing
bothern Switch	to light there was NO
Continuity meaning	to light there was NO there is a fault for suitch line erlais required to fix the fault to light
Brief description including mate	erials required to fix the fault the high h

Rewiring of line conductor from switch to light, 1.5 mm single core, other conductors do not need to be required as no faults on any tests to suggest they are damaged/need replacing.

Actions required to ensure rectification is suitable

Continuity, earth fault loop impedance and insulation resistance tests after work is carried out.

Iob card reference number: WK5 Candidate name: Description of work done/ tests carried of the solution of t	
Description of work done/ tests carried of	out to locate fault (if any)
Con ohms / continuity to	
Con ohing / continuity to	
nsulation resistance too	t Format Light, Short between Switch
Visaal - Inspection	
The nature of the fault	
Live & East conducto	ers have come into
contern in the circult In Solation de SZB fance	In adience he have no harvoure
Brief description including materials req	uired to fix the fault
Auto circuit is in Na Meaning free wiring is m	on - metalic conduit - acsessable, I would suggest
	gle core cables, this would
be the correct way to	Fix the fault as there were
Actions required to ensure rectification i	in spection ins manied eut.

Task 3 Fault Report Sheet

Job card reference number:

QA1 Candidate name:

Date of assessment:

Description of work done/ tests carried out to locate fault (if any)

Continuity of earth between main consumer unit and workshop consumer unit, showing no result.

The nature of the fault

No continuity between main consumer unit and workshop consumer unit.

Brief description including materials required to fix the fault

Earth 6mm needs replacing

Actions required to ensure rectification is suitable

Continuity test between consumer unit (main) and worshop consumer unit after works.

Task 3 Fault Report Sheet		
Job card reference number: QA1		
Candidate name:	Date of assessment:	
Description of work done/ tests carried ou		
Continuity of Earth,	Neutral, Line,	
error on line condo	ctor, kested from	
Cu fo Switch than c	u to light then	
Cu fo Switch then cu to light then Switch by light		
The nature of the fault		
Break in the line conductor from consumer unit to switch resulting in no continuity.		
Brief description including materials required to fix the fault		

Replace line from consumer unit to switch.

Actions required to ensure rectification is suitable

Continuity test after work completed. Insulation resistance and EFL impedence.

Task 3 Fault Report Sheet

Job card reference number: 13HS

Candidate name:

Date of assessment:

Description of work done/ tests carried out to locate fault (if any)

confirmity of All conductors to

Viscol (nspection

The nature of the fault

No neutral continuity from board to light

Brief description including materials required to fix the fault Neutral rewire in 1.5 mm single core cable because all other wiring was correctly tested.

Actions required to ensure rectification is suitable Continuity test on neutral conductor after work completed.

Task 3 Fault Report Sheet		
Job card reference number: QA3		
Candidate name:	Date of assessment:	
Description of work done/ tests carried ou	t to locate fault (if any)	
contincity of Ci loscilling in incorrect Strappers	and L.Z stippers	
losalting in Incorrect	connection of	
Strappors		
The nature of the fault		
la correct conoction of	Strappers	
Brief description including materials required to fix the fault Reconnect correctly, L1 and L2 in correct positions		
Actions required to ensure rectification is Continuity test after works.	suitable	

Practical Observation (PO) Form (Task 3)

8710-33 T Level Technical Qualification in Building Services Engineering for Construction

8710-353 Electrotechnical Engineering (Summer 2023)

Candidate name	<first name=""> <surname></surname></first>
City & Guilds candidate No.	ABC1234
Date	27/04/2023

Provider name	<provider name=""></provider>
City & Guilds Provider No.	999999a

Task 3 assessment themes:

- Health and safety
- Systems and components
 - Documentation
 - Technical information
- Reports and information
- Handover and communication
- Working with faults

Record observation notes below to inform internal marking and external moderation. Notes must be detailed, accurate and differentiating which use terminology from the mark grid along with specific examples observed. Notes must identify areas of strength and weakness, distinguish between different qualities of performance and to facilitate accurate allocation of marks once all evidence has been submitted.

Assessment theme	Assessor observation notes
Health and safety • Risk assessment • Risk mitigation • Harm and probability factors • Adherence to health and safety	Risk mitigation methods identified for some of the potential risks, but not all. Consideration given to potential for harm and probability factors. Health and safety is followed during preparation and throughout tasks and all work completed safely
Systems and components (Installation) • Installation procedure • Appropriate component selection • Confidence and competence displayed in	Installation to industry standards and is completed in a timely manner. Component selection appropriate and clearly links to the quality of finished installation. Confidence and competence displayed in the installation process with levels of skills shown in the quality of the finished installation. Use of tools is excellent resulting in a near high-quality installation. Candidate follows manufacturer's instructions at most stages of the installation.

installation process • Ability to use appropriate tools • Following manufacturer's instructions	Measurement wiring and associated components is to a sound standard with clear attempts to meet industry levels, resulting in an install that has few errors from the proposed installation plan.
Systems and components	Consideration of implications of sequence for dismantling, minimising damage to parts that could be recycled.
 (Decommissioning) Consideration of implications of sequence Salvage of materials for recycling Designation and categorisation for 	Use of removal techniques to salvage as much materials as possible for recycling. All removed materials and equipment suitably designated and categorised for disposal as required.
disposal	
Reports and information	Consistently use industry terminology appropriately in both written and verbal contexts.
 Technical 	Certification and schedules completed with minimal but accurate detail in all aspects.
Handover and	Handover considered and well organised/ structured and all
communication • Detail / explanations • Consideration of client perspective • Communication style • Customer care skills	elements explained. Consideration of client perspective and requirements, confirmation of understanding sought.
 Working with faults Fault finding technique Reference to / follows manufacturer's instructions Rectification of faults 	Fault-finding techniques carried out systematically and logically displaying accurate knowledge of faultfinding techniques. Candidate follows manufacturer's instructions at most stages of the task. Rectification of faults follows logical process and systems is operational.

Any other aspects

Good fault-finding techniques showing the confidence and ability required.

Internal assessor signature	Date
	28/04/2023

If completing electronically, double click next to the 'X' to add an electronic signature once the record is **finalised**.



Get in touch

The City & Guilds Quality team are here to answer any queries you may have regarding your T Level Technical Qualification delivery.

Should you require assistance, please contact us using the details below:

Monday - Friday | 08:30 - 17:00 GMT

T: 0300 303 53 52

E: technicals.quality@cityandguilds.com

W: http://www.cityandguilds.com/tlevels

Web chat available here.

The T Level is a qualification approved and managed by the Institute for Apprenticeships and Technical Education.

Copyright in this document belongs to, and is used under licence from, the Institute for Apprenticeships and Technical Education, © 2023. 'T-LEVELS' is a registered trademark of the Department for Education. 'T Level' is a registered trademark of the Institute for Apprenticeships and Technical Education. 'Institute for Apprenticeships & Technical Education' and logo are registered trademarks of the Institute for Apprenticeships and Technical Education.

We make every effort to ensure that the information contained in this publication is true and correct at the time of going to press. However, City & Guilds' products and services are subject to continuous development and improvement, and the right is reserved to change products and services from time to time. City & Guilds cannot accept responsibility for any loss or damage arising from the use of information in this publication.

City & Guilds is a trademark of the City & Guilds of London Institute, a charity established to promote education and training registered in England & Wales (312832) and Scotland (SC039576). City and Guilds Group Giltspur House, 5-6 Giltspur Street London EC1A 9DE

